

BATTERY CABLE

- **ANCOR** Marine Grade™ wire is manufactured from tinned copper stranding for maximum protection against corrosion and electrolysis. Ultra flexible (Type 3) stranding resists fatigue due to vibration and flexing.
- **ANCOR**'s proprietary premium vinyl insulation stays flexible even in extreme cold and resists salt water, battery acid, oil, gasoline and ultra-violet radiation. Exclusive insulation is rated at 600 volts, 105° C dry and 75° C wet, and is resistant to heat and abrasion.
- Exceeds all UL 1426, US Coast Guard Charterboat (CFR Title 46) and ABYC standards.



8 - 2 AWG BATTERY CABLE

Cable Size	Color	Spool Length(ft)	Item Number
8 8 mm ²	Black	25	111002
		50	111005
		100	111010
		250	111025
		500	111050
		1000	111099
	Green	25	111302
		50	111305
		100	111310
		250	111325
		500	111350
	Red	25	111502
		50	111505
		100	111510
		250	111525
		500	111550
		1000	111599
	White	25	111702
		100	111710
		250	111725
500		111750	
1000		111799	
Yellow	25	111902	
	50	111905	
	100	111910	
	250	111925	
	500	111950	
	1000	111999	
6 13 mm ²	Black	25	112002
		50	112005
		100	112010
		250	112025
		500	112050
	750	112075	

Cable Size	Color	Spool Length(ft)	Item Number
6 13 mm ²	Green	25	112302
		50	112305
		100	112310
		500	112350
		750	112375
	Red	25	112502
		50	112505
		100	112510
		250	112525
		500	112550
		750	112575
	White	25	112702
		50	112705
		100	112710
		250	112725
500		112750	
Yellow	25	112902	
	50	112905	
	100	112910	
	500	112950	
	750	112975	
4 21 mm ²	Black	25	113002
		50	113005
		100	113010
		250	113025
		500	113050
	Red	25	113502
		50	113505
		100	113510
		250	113525
		500	113550
Yellow	25	113902	
	50	113905	
	100	113910	
	250	113925	
	500	113950	

UL 1426 Tinned Boat Cable

Cable Size	Color	Spool Length(ft)	Item Number
2 34 mm ²	Black	25	114002
		50	114005
		100	114010
		250	114025
		400	114040
	Red	25	114502
		50	114505
		100	114510
		250	114525
		400	114540
Yellow	25	114902	
	50	114905	
	100	114910	
	250	114925	
	400	114940	

