

EVA gasket #2mm
NOT GLUED



Packaging **: pair in a white neutral box
included plastic bag with 8 screws 3,9x25 TC stainless steel 2 ISO cables
**See P8010



Coaxial 2-way Speaker , Waterproof Marine


Specifications

Nominal Impedance 4ohm
Voice Coil Resistance Rcc 3.6ohm ±15%
Resonance Frequency 80Hz ±15%
Efficiency SPL 87dB ±3dB (IEC-268.5)
Frequency Response 100Hz-20KHz @-15dB
Max Power short term 200W (IEC-268.5)
Max Power long term 30W (IEC-268.5)
Magnet type : Barium Ferrite, Ceramic
Magnet size : 72x32x10mm
Tweeter type : 36mm Neodymium , BD PEI diaphragm
Speaker weight 550gr. ±10%
Protection level : IP55
Salt spray resistant (CEI EN 600068-2-11)
Material : ASA (UV resistant)
Colour : RAL 9003

Integrated grille assembly and Cast Polymer Baskets are used to provide a waterproof and UV resistant platform. The spider and finel leads are treated against moisture and UV contamination for marine applications. High quality Balanced Dome PEI diaphragm Tweeter, is used for waterproof properties and perfect frequency extension out to 20KHz. The tweeter is mounted ahead of the woofer allowing the motor structure to be sealed off from moisture.

Mastercarton Details

(Printing both sides) :
Pt.No: 051-018-011
Qty : 10 pairs
G.W. : 15 Kg
N.W. : 12,5 Kg
Made in China



00		02/04/2010	FIRST ISSUE	MINTEGAZZA G.	
ISSUE	DATE	MODIFICATION		DRAWN	APPROVED
THIS DOCUMENT HAS BEEN ENGINEERED BY CAD SYSTEM. HAND MADE MODIFICATIONS ARE NOT ALLOWED.					
ALL UNCHECKED SPEAKERS ARE IN USE		TITLE MARINE SPEAKER 051-018-011			
VDO		Scale:	Drawing No. 00090	PART No. 051-018-011	SHEET No. 1 of 1